

Reduce looseness and fine tune precision equipment assembly to a higher degree of accuracy.

Shims, Spacers, Whashers

Super precision shims, spacers, washers without dispersion in thickness enable high assembly precision. We provides shims for M2 to M8 as we standard shim. (Please refer to the price list below)



Why Spacer?

Precision Supplies shims with tolerance of thickness ±0.5µm or

±1µm in compliance with the customers' requirements.

Low Cost Provide a shim from one piece as par the below price list.

Prompt Delivery Standard type shims can be shipped on the day of your

order if stocks are available.

Convenience We also accept materials and shapes different from our


standard shim on request.

Specification for Standard Shim

Super Precision Shim

- · Material SUS304
- Thickness Tolerance ±1µm (0.001mm)
- · Measurement Equipment Mitsutoyo Laser Hologage

Precise adjustment is available for assembling of precision equipment, mold and jig. We can provide not only standard shim as per the below drawing but also any other shapes like washer or square.



We can provide not only standard shim but also shims in any other shapes and sizes on request.

Processing Achievement

Type	Size a(mm)	Size b(mm)	±1um (JPY) *Excluding Tax	±1um (JPY) *Excluding Tax
For M2,M3	3.3	6.5	@400	@600
For M4	4.5	8	@460	@690
For M5	5.5	10	@550	@830For
For M6	6.5	12	@650	@980
For M8	8.5	16	@850	@1,280

Thickness Size t(um)

10,11,12,13,14,15,16,17,18,19,20,30,40,50,60,70,80,90,100

Mirror Fit Spacer

We developed a "Mirror fit spacer" with mirror polished surface, not affecting the volume of variation in assembling equipments, contributing to the stability of dimensions.



Surface Roughness Ra 1nm



Surface Roughness Ra 80nm

^{*}Provide a shim from one piece.

^{*}The prices do not include any transportation charge.

^{*}The price do not include any tax.

[•]From one piece to large scale production •From material procurement to all processing processe

[•] For more information on delivery time, price and other specifications, please contact us as follows